

TL12HO-48-9XX-5-XX Indoor LED Tape Light




Ultra thin flexible LED strip
 Modern contemporary design
 Simple to install
 Available in 16.4' (5M) rolls
 High CRI >90



Optional moisture proof silicone coating

Solderless connectors make it easy to connect strips together after cutting.



Requires LED 12V DC driver (sold seperately)

Product Specifications:

Electrical:

Input Voltage - DC 12 Volts
 Power Consumption - 3.5W/foot
 (11.5 W/M)
 Dimmable
 Approved for use in Damp Locations

Optical:

15 - 5050 chips per foot (48/meter)
 Color Temperatures - 3000K, 5500K
 Lumens - 360/foot (1180/meter)
 Beam Spread - 140°

Mechanical:

Cutttable every 3 LEDs - 2.44" (62mm)
 L197" x W0.4" x H0.08"
 L5000mm x W10mm x H2mm
 Optional moisture proof silicone coating
 3M double sided tape on back



Project:	Quantity:
Product Code: (Please select light requirements)	
TL12HO - 48 - 9	- 5 -
High Output Tape Light	30 = CRI >90, 3000 K 55 = CRI >90, 5500 K
	MP = Moisture Proof
eg. TL12HO-48-930-5-MP	

Twice Bright Lighting Co. Ltd.

108 - 11860 Hammersmith Way · Richmond, BC · Canada · V7A 5G1
 (778) 297-2121 · (888) 484-7295 · info@twicebright.com · www.twicebright.com