

## DR - 12V / 24V DC LED Drivers/Power Supplies

### 12VDC DRIVERS/POWER SUPPLIES

	DESCRIPTION	ORDER CODE	VOLTAGE	WATTAGE	OUTPUT	DIMENSIONS	WIRING:
NON-DIMMING	15W 12VDC LED PSU	DR-15W12VDC	120VAC	15W MAX	12VDC	L4.37 X W1.81 X H0.79 in.	<input checked="" type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
	30W 12VDC LED PSU	DR-30W12VDC	120VAC	30W MAX	12VDC	L7.30 X W1.14 X H0.79 in.	<input checked="" type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
	30W Outdoor LED PSU	DR-30W12VDC-OUT	100-130VAC	30W MAX	12VDC	L7.30 X W1.14 X H0.79 in.	<input type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
	60W Outdoor LED PSU	DR-60W12VDC-OUT	100-130VAC	60W MAX	12VDC	L7.44 X W1.89 X H1.30 in.	<input type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
	150W Outdoor LED PSU	DR-150W12VDC-OUT	100-265VAC	150W MAX	12VDC	L9.40 X W2.80 X H1.77 in.	<input type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
	240W Outdoor LED PSU	DR-240W12VDC-OUT	100-277VAC	240W MAX	12VDC	L9.60 X W2.70 X H1.54 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
DIMMING	24W Dimmable LED PSU	DR-24W12VDC-DIMA	120VAC	24W MAX	12VDC	L6.10 X W2.13 X H0.79 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	45W Dimmable LED PSU	DR-45W12VDC-DIMA	120VAC	45W MAX	12VDC	L7.09 X W2.40 X H0.98 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	60W Dimmable LED PSU	DR-60W12VDC-DIMA	120VAC	60W MAX	12VDC	L7.09 X W2.36 X H1.38 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	60W Dimmable LED PSU	DR-60W12VDC-DIMM	120VAC*	60W MAX	12VDC	L6.55 x W2.25 x H2.55 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	150W Dimmable LED PSU	DR-150W12VDC-DIMM	120VAC*	150W MAX	12VDC	L9.80 x W3.00 x H3.00 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	300W Dimmable LED PSU	DR-300W12VDC-DIMM	120VAC*	300W MAX	12VDC	L9.80 x W4.20 x H3.50 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
CLASS II	120W Dimmable LED PSU	DR-120W12VDC-DIMM-II	120VAC	120W MAX	12VDC	L11.33 X W4.73 X H4.26 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	180W Dimmable LED PSU	DR-180W12VDC-DIMM-II	120VAC	180W MAX	12VDC	L11.33 X W4.73 X H4.26 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	300W Dimmable LED PSU	DR-300W12VDC-DIMM-II	120VAC	300W MAX	12VDC	L11.33 X W4.73 X H4.26 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG

### 24VDC DRIVERS/POWER SUPPLIES

	DESCRIPTION	ORDER CODE	VOLTAGE	WATTAGE	OUTPUT	DIMENSIONS	WIRING:
NON-DIMMING	60W 24VDC LED PSU	DR-60W24VDC	120VAC	60W MAX	24VDC	L4.37 X W1.81 X H0.79 in.	<input type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
	120W 24VDC LED PSU	DR-120W24VDC	120VAC	120W MAX	24VDC	L7.30 X W1.14 X H0.79 in.	<input type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
	150W Outdoor LED PSU	DR-150W24VDC-OUT	100-265VAC	150W MAX	24VDC	L9.40 X W2.80 X H1.77 in.	<input type="checkbox"/> HARDWIRE <input checked="" type="checkbox"/> PLUG
	240W Outdoor LED PSU	DR-240W24VDC-OUT	100-277VAC	240W MAX	24VDC	L9.60 X W2.70 X H1.54 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
DIMMING	60W Dimmable LED PSU	DR-60W24VDC-DIMA	120VAC	60W MAX	24VDC	L7.09 X W2.36 X H1.38 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	96W Dimmable LED PSU	DR-96W24VDC-DIMM	120VAC*	96W MAX	24VDC	L6.55 x W2.25 x H2.55 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
CLASS II	192W Dimmable LED PSU	DR-192W24VDC-DIMM-II	120VAC	120W MAX	24VDC	L11.33 X W4.73 X H4.26 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG
	288W Dimmable LED PSU	DR-288W24VDC-DIMM-II	120VAC	180W MAX	24VDC	L11.33 X W4.73 X H4.26 in.	<input checked="" type="checkbox"/> HARDWIRE <input type="checkbox"/> PLUG

\*These drivers are available in 277V. Other driver sizes are available.