


SM12HO-XXX - 12V LED Sign Modules

SM12HO-2-860-25 (6000K Cool White) SM12SO-2-830-25 (3000K Warm White)




VOLTAGE:	12V
WATTAGE:	.66W
SPREAD:	140°
LUMENS:	75

CALCULATIONS	
WATTS:	0.66
QTY:	X
= TOTAL WATTAGE:	

2 LEDS 0.66 Watts per module L1.5" x W0.6" x H0.4"
10 ft. length includes 25 modules with 4.5" wire length between modules

SM12HO-3-860-25 (6000K Cool White)




VOLTAGE:	12V
WATTAGE:	1W
SPREAD:	140°
LUMENS:	75

CALCULATIONS	
WATTS:	1
QTY:	X
= TOTAL WATTAGE:	

3 LEDS 1 Watt per module L2.4" x W0.6" x H0.4"
12.5 ft. length includes 25 modules with 3.5" wire length between modules

SM12HO-3-RGB-25 (Color changing. Requires RGB controller)



VOLTAGE:	12V
WATTAGE:	1W
SPREAD:	140°
LUMENS:	75

CALCULATIONS	
WATTS:	0.75
QTY:	X
= TOTAL WATTAGE:	

3 LEDS 1 Watt per module L3.5" x W0.5" x H0.25"
12.5ft length includes 25 modules with 3" wire length between modules



- Durable & long lasting +70,000 hours
- Simple Installation using 3M tape on Back or with screw tabs
- Integrated lens for better light dispersement
- Outdoor rated IP66
- Dimmable

POWER SUPPLY*

PSU	PART #	INPUT	WATTAGE	OUTPUT	DIMENSIONS	CALCULATIONS	QUANTITY
30W Driver	DR-30W12VDC-OUT	100-130V	30W MAX	12VDC	L7.30 X W1.14 X H0.79 in.		<input type="text"/>
60W Driver	DR-60W12VDC-OUT	100-130V	60W MAX	12VDC	L7.44 X W1.89 X H1.30 in.		<input type="text"/>
150W Driver	DR-150W12VDC-OUT	100-265V	150W MAX	12VDC	L9.40 X W2.80 X H1.77 in.		<input type="text"/>
240W Driver	DR-240W12VDC-OUT	100-277V	240W MAX	12VDC	L9.60 X W2.70 X H1.54 in.		<input type="text"/>

* Dimming drivers are available.