

Date: _____	Job: _____	Type: _____
Notes: _____		Quantity: _____




The MSW1 LED step/wall light uses a single chip COB and an acrylic lens. It's aluminum housing lends to its durability. These step/wall lights are great for interior and exterior step lighting applications. They are also used in millwork applications.

IP67

Technical Specifications:

Operating Voltage	12VDC
Power Consumption	1W
Lumens Delivered (3000K)	63lm
Efficacy (3000K)	63lm/W
IES File (3000K)	
LED Chips	COB
Color Temperatures	2700K, 3000K, 4000K, 5000K
CRI	90+
MacAdam Ellipse Binning	3-step
Beam	30°
Dimmable	YES
Housing	Aluminum
Trims	Steel
Warranty	5 years

Dimensions:



Trims:



RS - Round Scoop
(scoop removed)



RS - Round Scoop
Ø1.54"




RL - Round Louver
Ø1.54"



MR - Medium Round
Ø2.00"




LR - Large Round
Ø2.75"



SSS - Stainless Steel Square
1.54 x 1.54"



SS1 - Stainless Steel 1-Way
Ø1.80"



SS2 - Stainless Steel 2-Way
Ø1.80"

Ordering Code:

MSW1	-	121	-		-		-	
------	---	-----	---	--	---	--	---	--

CCT

27K - 2700K
3K - 3000K
4K - 4000K
5K - 5000K

TRIM





RS - Round Scoop
RL - Round Louver
MR - Medium Round
LR - Large Round*
SSS - Stainless Steel Square**
SS1 - Stainless Steel 1-Way**
SS2 - Stainless Steel 2-Way**

FINISH

BL - Black
BS - Brushed Steel
WH - White

*Only available in Brushed Steel, **304 Stainless Steel

Driver Cutsheets:

DESCRIPTION	INPUT	OUTPUT	WATTAGES	SPECIFICATION SHEETS
Non-Dimming Indoor	120VAC	12VDC	15W, 30W	DR-12VDC 
Non-Dimming Indoor/Outdoor	120VAC	12VDC	30W-264W	DR-12VDC-OUT 
Universal Phase Dimming Indoor	120VAC	12VDC	24W 48W 60W	DR-12VDC-DIMA 
Univ. Phase/0-10V Dimming Ind./Out.	100-277VAC	12VDC	30W-300W	DR-12VDC-DIMS-UNV 

Voltage Drop Calculator:

Wire Gauge Calculator - Load vs AWG vs Max. Distance Away From Driver

LOAD	10W	20W	30W	40W	50W	60W
WIRE GAUGE						
20AWG	18 ft	9 ft	6 ft	5 ft	4 ft	3 ft
18AWG	34 ft	17 ft	11 ft	8 ft	6 ft	5 ft
16AWG	54 ft	27 ft	18 ft	13 ft	10 ft	9 ft
14AWG	86 ft	43 ft	29 ft	21 ft	17 ft	14 ft
12AWG	134 ft	68 ft	45 ft	34 ft	27 ft	22 ft
10AWG	199 ft	99 ft	66 ft	49 ft	39 ft	33 ft