

Date: _____ Job: _____ Type: _____
 Notes: _____

IP66



SM12HO-2-830-25 (3000K) - SM12HO-2-860-25 (6000K)



- 2 LEDs per module
- 0.66W per module
- module dimensions L1.5" x W0.6" x H0.4"
- one string (12.5ft length) includes 25 modules
- 4.5" of wire between modules

VOLTAGE:	12V
WATTAGE:	.66W
SPREAD:	140°
LUMENS:	54

SM12HO-3-860-25 (6000K)



- 3 LEDs per module
- 1W per module
- module dimensions L2.4" x W0.6" x H0.4"
- one string (12.5ft length) includes 25 modules
- 3.5" of wire between modules

VOLTAGE:	12V
WATTAGE:	1W
SPREAD:	140°
LUMENS:	75

SM12HO-3-RGB-25



- 3 LEDs per module
- .75W per module
- module dimensions L3.0" x W0.6" x H0.4"
- one string (12.5ft length) includes 25 modules
- 3.0" of wire between modules

VOLTAGE:	12V
WATTAGE:	.75W
SPREAD:	140°
LUMENS:	60

Driver Cutsheets:

DESCRIPTION	INPUT	OUTPUT	WATTAGES	SPECIFICATION SHEETS
Universal Dimming Indoor/Outdoor	100-277VAC	12VDC	30W-150W	DR-12VDC-DIMS-UNV
Non-Dimming Indoor/Outdoor	100-265VAC	12VDC	30W-264W	DR-12VDC-OUT
RGB Controller Outdoor	12-36VDC	12-36VDC	480W max.	DR-RGBW-WIFI-CON-OUT
5 Channel DMX Decoder	12-24VDC	12-24VDC	768W max.	DR-DMX-5CH-DEC
RGBW DMX Controller	12-36VDC	12-36VDC	N/A	DR-DMX-RGBW-CON