


PROJECT	TYPE	NOTES
IP66 		

SM12HO-2-830-25 (3000K) - SM12HO-2-860-25 (6000K)



- 2 LEDs per module
- 0.66W per module
- module dimensions L1.5" x W0.6" x H0.4"
- one string (12.5ft length) includes 25 modules
- 4.5" of wire between modules

Voltage	12V
Wattage	.66W
Spread	140°
Lumens	54

SM12HO-3-860-25 (6000K)



- 3 LEDs per module
- 1W per module
- module dimensions L2.4" x W0.6" x H0.4"
- one string (12.5ft length) includes 25 modules
- 3.5" of wire between modules

Voltage	12V
Wattage	1W
Spread	140°
Lumens	75





SM12HO-3-RGB-25



- 3 LEDs per module
- .75W per module
- module dimensions L3.0" x W0.6" x H0.4"
- one string (12.5ft length) includes 25 modules
- 3.0" of wire between modules

Voltage	12V
Wattage	.75W
Spread	140°
Lumens	60

DRIVER CUTSHEETS

DESCRIPTION	INPUT	OUTPUT	WATTAGES	SPECIFICATION SHEETS	
Universal Dimming Indoor/Outdoor	100-277VAC	12VDC	30W-150W	DR-12VDC-DIMS-UNV	
Non-Dimming Indoor/Outdoor	100-265VAC	12VDC	30W-264W	DR-12VDC-OUT	
RGB Controller	12-36VDC	12-36VDC	480W max.	DR-RGBW-WIFI-CON	
5 Channel DMX Decoder	12-24VDC	12-24VDC	768W max.	DR-DMX-5CH-DEC	
RGBW DMX Controller	12-36VDC	12-36VDC	N/A	DR-DMX-RGBW-CON	