

Date: _____	Job: _____	Type: _____
Notes: _____		Quantity: _____



The ML-HIL series, backlit illuminated mirrors, adds a modern touch to any project. High efficacy LED chips produce outstanding illumination. With a plethora of options including different sizes, lumen packages, color temperatures, anti-fog, and touch or hardwired power, the ML-HIL will satisfy most requirements. The ability to be mounted in portrait or landscape orientation adds to the versatility of these mirrors.



### Technical Specifications:

Operating Voltage	110-240VAC
Power Consumption	45W-100W
Efficacy (6500K)	173lm/W
Color Temperatures	2700K, 3000K, 3500K, 4000K, 5000K, 6500K,
CRI	90+
IP Rating	IP44
Location Rating	Dry & Damp Locations
Minimum Length	24"
Maximum Length	60"
LED Life	50,000 hrs
Warranty	3 years

### Ordering Code:

ML - 
 HIL - 
  - 
  - 
  - 
  -

**WATTAGE**  
- min. 45W max. 100W

**CRI / CCT**  
**927** - 90+ / 2700K  
**930** - 90+ / 3000K  
**935** - 90+ / 3500K  
**940** - 90+ / 4000K  
**950** - 90+ / 5000K  
**965** - 90+ / 6500K

**DIMMING**  
 - Non-dimming  
**PH** - Phase dimming  
**010** - 0-10V dimming

**LENGTH**  
- min. 24" max 60"

**WIDTH**  
- min. 24" max 60"